rf IDEAS

Our smallest and most capable desktop reader yet supports nearly all proximity and contactless credentials worldwide.

The small yet powerful credential reader has an extensive feature set that includes:

- Four ID card configurations (2 are pre-set and all four are user definable)
- Auto-tuning for 13.56 MHz antenna to optimize performance in various environments
- User-selectable volume control including a beeper on/off setting
- Support for iCLASS[®] ID, SE and Seos[®] (800 models only)
- New compact and modern design
- Articulated cable and rubber feet provide secure desktop placement

Superior Security just got Smaller

The versatile WAVE ID Plus Mini reader combines proximity and contactless technologies into one reader that has the ability to hold four card configurations, enabling growing organizations to seamlessly integrate different ID card technologies. These credential readers are designed for customers seeking to leverage their existing card system for applications beyond building access.

Developed to read virtually any proximity or contactless card type in the world, the WAVE ID Plus Mini is the most powerful, robust reader on the market for identification, authentication, and access applications. Credential-based reader solutions eliminate the need to manually enter user names and passwords, streamlining workflow and eliminating errors for identification.

WAVE DO'I PLUS

Expanding Credential Identification Beyond Physical Access

The WAVE ID Plus Mini reader easily integrates into existing card access systems, allowing companies to leverage the same cards they use to get into the building for countless applications involving logical access to network, software applications, and equipment. Connecting directly into the USB port, the reader emulates keystrokes of the USB model card data on the login screen. Its plug-and-play functionality requires no software for seamless integration with common operating systems and applications.

Developer-Friendly SDK

Software Developer Kits (SDKs) allow independent programmers to develop and enable their applications with the ability to read ID card identification information directly off any of the proximity, contactless or magnetic swipe cards in use today. Software developers can easily create a solution that leverages the use of employee ID card data, resulting in added benefits to their applications such as single sign-on, QA tracking, cashless cafeteria, industrial vending or attendance.



Trust begins here.™



Common Applications

The introduction of the card reader which accommodates four configurations paves the way to an unlimited number of applications. Here are some of the most common applications in key industries.

	HEALTHCARE	GOVERNMENT	MANUFACTURING	ENTERPRISE
Single Sign-on	+	+	+	+
Time & Attendance	+	+	+	+
Training Compliance	+	+	+	+
Point-of-Sale	+	+	+	+
Secure Print Management	+	+	+	+

STANDARD FEATURES

Model Series	RDR-80531BKU, WAVE ID Plus Mini Black Keystroke USB Reader RDR-80532BKU, WAVE ID Plus Mini Black SDK USB Reader RDR-80031BKU, WAVE ID Plus Mini w/iCLASS SE & Seos Black Keystroke USB Reader RDR-80032BKU, WAVE ID Plus Mini Black w/iCLASS SE & Seos SDK USB Reader	
Operating Frequency	125/132 kHz and 13.56 MHz	
Interface	USB	
SDK available for writing apps to the reader	Yes	
PHYSICAL CHARACTERISTICS		
Dimensions (inches)	Length 2.9" (74mm); Width 1.7" (42mm); Height 0.5" (13mm)	
Weight	2.5 ounces (72g) with a 6' cable	
Housing Color	Black (gray inlay)	
Cable Length	6' standard; Contact rf IDEAS for other options	
Indicators	LED indicator; Adjustable beeper volume (off, low, medium, high)	
Form Factors	Desktop	
Power Supply	USB self-powered	
Power Consumption	65 mA typical, 185 mA maximum	
ENVIRONMENT		
Operating Temperature Range	-13° to 150°F (-25° to 65°C)	
Operating Humidity Range	5% to 95% relative humidity, non-condensing	
Storage Temperature Range	-40° to 185°F (-40° to 85°C)	
OTHER		
Certifications (Please contact rf IDEAS for information about other global certifications)	FCC-United States; CE Mark-Europe; RCM-Australia; IC-Industry Canada; UL Environmental: RoHS, REACH	
Compatible Operating Systems	Windows XP®, 7®, 8®, 10® and Linux (Ubuntu, Red Hat), macOS and Android (keystroking and SDK only)	
Configuration Tools	rf IDEAS Configuration Utility and Smartcard Manager Utility, available on rf IDEAS support page	
Card Types	Supports nearly all card types worldwide. Visit rfIDEAS.com for full list of supported card types.	

rf IDEAS® and WAVE ID® are registered trademarks of rf IDEAS, Inc. Trademarks not belonging to rf IDEAS are property of their respective companies.

©2021 rf IDEAS, Inc. All rights reserved. Products are subject to change without notice.